

Description


Local Area Network Cable

Cat. 7A S/FTP 4x2xAWG23/1 orange LSZH
1000MHz - 30% Braid Coverage



Data Sheet

LAN7A10004573ZHA



Ø	0,57	1,35		8,0
	(Cu)	(PEG)	(Al/Pet)	(CuSn)
				(LSZH)

Class CPR acc. to UE 305/2011 (DoP)

Dca s1a,d1,a1

The cable can be used in the field of application of the Construction Product Regulation (DoP) UE nr. 305/2011 for the class of performance specified on the related product label.

Standards

ISO/IEC 11801 Class Fa	EN 50288-9-1	EN 50173	IEC 61156
EIA-TIA 568	CEI-UNEL 36762		

Reaction to Fire

EN50575

Application

Primary (Campus), Secondary (Riser), Tertiary (Horizontal)
IEEE 802.3: 10Base-T; 100Base-T; 1000Base-T; 10GBase-T
IEEE 802.5 16 MB: ISDN; TPDDI; ATM
Power over Ethernet (PoE)/PoE+

Construction data

Inner conductor of plain copper	(Cu)	Ø 0,57	mm
Insulation of physical foam Polyethylene	(PEG)	Ø 1,35	mm
Al/Pet foil shielded pairs, PiMF mode	(Al/Pet)		

Composition

Twisted pairs, coloured by Standard TIA-568A

Braid of tinned copper wires	(CuSn)		
Braid Optical Coverage		30	%
Outer sheath of Thermoplastic material - orange (RAL 2003) - halogen-free, low smoke, flame retardant and UV-resistant	(LSZH)	Ø 8,00	mm

Printed each meter by blue ink-jet :

CAVEL LAN 7A 1000 4573 ZHA MADE IN ITALY CAT 7A S/FTP 4x2xAWG23/1 Euroclass Dca s1a, d1, a1 ISO-IEC 11801 EN50173-1 CEI-UNEL 36762 C-4 (U0 = 400V) gggaan m

(gggaan=batch number m=meter marking)

ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli
Tel +39-382.815150 Fax +39-0382.814212

Date

28/09/2020

Responsible

A. Bergaglio

Description

Local Area Network Cable

Cat. 7A S/FTP 4x2xAWG23/1 orange LSZH
1000MHz - 30% Braid Coverage

Coaxial Cables

CAVEL[®]

since 1968

Data Sheet

LAN7A10004573ZHA

Physical data

Weight of copper conductors	22,90	kg/km
Total weight of cable	66,00	kg/km
Minimum bending radius x1/n	40/80	mm
Max.Tensile Strength	150	N
Installation temperature	0 / +50	°C
Operating temperature	-20 / +60	°C

Electrical data

Characteristic impedance	100 MHz	100 ± 5	Ohm
Capacitance of Twisted Pair (@800Hz)		43	pF/m
Velocity Ratio		77 %	
DC Conductor Resistance		73	Ohm/km
Loop resistance		146	Ohm/km
Insulation resistance		> 5000	MOhm/km
Sheath Insulation Voltage (DC, 1 min)		1	kV
Coupling Attenuation		> 45	dB

Screening Attenuation (SA)

30 - 100 MHz	> 70 dB
100 - 1000 MHz	> 60 dB

Transfer Impedance (Zt)

1 MHz	< 11 mOhm/m
10 MHz	< 7 mOhm/m
30 MHz	< 6 mOhm/m

Transmission-Characteristic (at 20°C)

Frequency [MHz]	Attenuation [dB/100m]	RL [dB]	NEXT [dB]	ACR-N [dB/100m]
1	2,10	25,00	90,00	87,90
4	3,60	25,00	90,00	86,40
10	5,40	25,00	90,00	84,60
16	6,80	25,00	90,00	83,20
20	7,70	25,00	85,00	77,30
31,25	9,60	25,00	85,00	75,40
62,5	13,70	25,00	80,00	66,30
100	17,40	25,00	80,00	62,60
155,5	21,90	25,00	80,00	58,10
250	28,10	25,00	75,00	46,90
450	38,30	25,00	70,00	31,70
600	44,80	20,00	65,00	20,20
750	51,00	20,00	65,00	14,00
900	54,50	20,00	65,00	10,50
1000	58,00	20,00	65,00	7,00

ITALIANA CONDUTTORI s.r.l.Viale Zanotti 90 I - 27027 Gropello Cairoli
Tel +39-382.815150 Fax +39-0382.814212

Date

28/09/2020

Responsible

A. Bergaglio